

#4
6/28/92
pm

The
**Patent
Office**

The Patent Office
Cardiff Road
Newport
Gwent
NP9 1RH


RECEIVED
93 JUN 24 AM 10:15
GROUPE

I, the undersigned, being an officer duly authorised in accordance with Section 62(3) of the Patents and Designs Act 1907, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the Patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or the inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 13 NOV 1992

For official use



119 NOV 1991

21NOV'91H002E2698

PAT 1 77 UC

15.00

Your reference

P6930GB-NF/jsd

Notes

Please type, or write in dark ink using CAPITAL letters. A prescribed fee is payable for a request for grant of a patent. For details, please contact the Patent Office (telephone 071-438 4700).

Rule 16 of the Patents Rules 1990 is the main rule governing the completion and filing of this form.

Do not give trading styles, for example, 'Trading as XYZ company', nationality or former names, for example, 'formerly (known as) ABC Ltd' as these are not required.

Warning

After an application for a Patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977 and will inform the applicant if such prohibition or restriction is necessary. Applicants resident in the United Kingdom are also reminded that under Section 23, applications may not be filed abroad without written permission unless an application has been filed not less than 6 weeks previously in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction revoked.

The
Patent
Office

Request for grant of a Patent

Form 1/77

Patents Act 1977

1 Title of invention

1 Please give the title of the invention

IMPROVEMENTS IN OR RELATING
TO A STAPLING MACHINE

2 Applicant's details

☐ First or only applicant

2a If you are applying as a corporate body please give:

Corporate name

OFREX GROUP HOLDINGS PLC

Country (and State of incorporation, if appropriate)

GB

2b If you are applying as an individual or one of a partnership please give in full:

Surname

Forenames

2c In all cases, please give the following details:

Address

THE LODGE,
HARMONDSWORTH LANE,
HARMONDSWORTH,
WEST DRAYTON,
MIDDLESEX

UK postcode (if applicable)

UB7 OLQ

Country

ADP number (if known)

641142001 *H

2d, 2e and 2f: If there are further applicants please provide details on a separate sheet of paper.

☐ **Second applicant (if any)**

2d If you are applying as a corporate body please give:

Corporate name

Country (and State
of incorporation, if
appropriate)

2e If you are applying as an individual or one of a partnership please give in full:

Surname

Forenames

2f **In all cases**, please give the following details:

Address

UK postcode
(if applicable)

Country

ADP number
(if known)

3 An address for service in the United Kingdom must be supplied

Please mark correct box

3 Address for service details

3a Have you appointed an agent to deal with your application?

Yes ☒ No ☐ → go to 3b

↓
please give details below

Agent's name **FORRESTER KETLEY & CO.**

Agent's address **FORRESTER HOUSE,
52 BOUNDS GREEN ROAD,
LONDON**

Postcode **N11 2EY**

Agent's ADP
number **00000133001** ✓

3b: If you have appointed an agent, all correspondence concerning your application will be sent to the agent's United Kingdom address.

3b If you have not appointed an agent please give a name and address in the United Kingdom to which all correspondence will be sent:

Name

Address

Postcode

ADP number
(if known)

Daytime telephone
number (if available)

7 The answer must be 'No' if:

- any applicant is not an inventor
- there is an inventor who is not an applicant, or
- any applicant is a corporate body.

8 Please supply duplicates of claim(s), abstract, description and drawing(s).

Please mark correct box(es)

9 You or your appointed agent (see Rule 90 of the Patents Rules 1990) must sign this request.

Please sign here

A completed fee sheet should preferably accompany the fee.

7 Inventorship

7 Are you (the applicant or applicants) the sole inventor or the joint inventors.

Please mark correct box

Yes ☐

No ☒

A Statement of Inventorship on Patents Form 7/77 will need to be filed (see Rule 15).

8 Checklist

8a Please fill in the number of sheets for each of the following types of document contained in this application.

Continuation sheets for this Patents Form 1/77

Claim(s)

3

Description

13

Abstract

Drawing(s)

3

8b Which of the following documents also accompanies the application?

Priority documents (please state how many)

Translation(s) of Priority documents (please state how many)

Patents Form 7/77 – Statement of Inventorship and Right to Grant
(please state how many)

Patents Form 9/77 – Preliminary Examination/Search

Patents Form 10/77 – Request for Substantive Examination

9 Request

We request the grant of a patent on the basis of this application.

Forrester Ketley & Co.

Signed

Date

(day month year)

FORRESTER KETLEY & CO.

19

11

1991

Please return the completed form, attachments and duplicates where requested, together with the prescribed fee to either:

☐ The Comptroller
The Patent Office
Cardiff Road
Newport
Gwent
NP9 1RH

or

☐ The Comptroller
The Patent Office
25 Southampton Buildings
London
WC2A 1AY

4 Agent's or
applicant's reference
number (if applicable)

⑤ Claiming an earlier application date

5 Are you claiming that this application be treated as having been filed on the date of filing of an earlier application?

Yes ☐ No ☒ ➡ **go to 6**

↓
please give details below

number of earlier application or patent number

☐ filing date (day month year)

☐ and the Section of the Patents Act 1977 under which you are claiming:

15(4) (Divisional) ☐ 8(3) ☐ 12(6) ☐ 37(4) ☐

6 *If you are declaring priority from a PCT Application please enter 'PCT' as the country and enter the country code (for example, GB) as part of the application number.*

Please give the date in all number format, for example, 31/05/90 for 31 May 1990.

⑥ Declaration of priority

6 If you are declaring priority from previous application(s), please give:

Country of filing	Priority application number (if known)	Filing date (day, month, year)

PATENTS ACT 1977
P6930GB-NF/jsd

DESCRIPTION OF INVENTION

"IMPROVEMENTS IN OR RELATING TO A STAPLING MACHINE"

THE PRESENT INVENTION relates to a stapling machine and more particularly relates to a stapling machine adapted for use in stapling items such as sheets of paper.

A typical stapling machine for use in stapling together sheets of paper comprises two main components which are pivotally connected together. One component carries an anvil which is adapted to clinch the ends of two arms present on a staple which is ejected from the other component. The other component includes a staple magazine adapted to contain a plurality of staples, the staple magazine having one end aligned with a staple ejection slot. Means are provided to bias the staples towards the staple ejection slot. An ejector blade can be moved through the staple ejector slot to eject a staple. Typically, the ejector blade is moved either by pressing the top of the component containing the staple magazine downwardly, or by operating an actuating lever if the stapling machine is of the "pliers" type.

A disadvantage that arises is that the staple is driven down towards the anvil solely by the force applied by the person operating the device, and if that force is not sufficient to cause the staple to penetrate cleanly through any sheets of paper located between the two components, then the staple may become deformed, and the stapling operation will not be carried out satisfactorily.

The present invention seeks to provide an improved stapling machine in which the above-described disadvantage of prior proposed stapling machines is obviated or reduced.

According to this invention there is provided a stapling machine for stapling together sheets of paper or the like, the stapling machine comprising a first component carrying an anvil adapted to clinch the ends of the arms of the staple, which is pivotally connected to a second component containing a magazine for staples, means defining a staple ejection slot, means for biasing staples within the magazine towards the staple ejection slot, and a staple ejector blade adapted to move through the staple ejection slot to eject a staple towards the anvil, the staple ejector blade being associated with an actuator element adapted to move the ejector blade, the actuator element being provided with means to retain the actuator spring in a first predetermined position until a predetermined force has been applied to the actuator element tending to bias the ejector blade downwardly, means being provided then to release the actuator element to permit the actuator element to move, driving the staple ejector blade.

Preferably the means adapted to retain the actuator element in position comprise a toggle having part adapted to engage part of the actuator element, the toggle being adapted to be moved to a position in which the toggle does not engage the spring when said predetermined force has been applied to the actuator element.

Conveniently the toggle is resiliently biased towards a position in which it engages the actuator element.

Advantageously the actuating element spring is a spring of substantially "U" shape, presenting two substantially parallel arms, one arm being connected to the staple ejection blade and being associated with said toggle, the other arm being movable, away from the first arm actuating element, to apply said predetermined force to the first element, means being provided to operate the toggle when the said other arm has been moved to apply said predetermined force.

Conveniently the toggle is provided with means adapted to engage the free end of the said other arm of the actuator spring when the actuator spring has been moved to apply said predetermined force.

One embodiment of the invention may be in the form of a pliers stapling machine, the stapling machine incorporating a manually operable actuating lever which is pivotally connected to the first component and which engages said actuator spring to effect operation of the stapling machine.

Preferably the actuating lever has roller means engaging the said other arm of said actuator spring.

Advantageously said roller means also engage the first arm of said actuator spring, and the actuating handle is provided with resilient means adapted to bias the actuating handle to an initial position, so that as the handle is biased towards the initial position the roller engages the actuating spring and moves the actuating spring to an initial position.

In order that the invention may be more readily understood, and so that further features thereof may be

appreciated, the invention will now be described, by way of example, with reference to the accompanying drawings in which

FIGURE 1 is a side view of the operative parts of a stapling machine, the alternate positions of some of the parts being shown in phantom,

FIGURE 2 is a view illustrating the toggle and associated spring in perspective, and

FIGURE 3 is an exploded view of another embodiment of the invention.

Referring to the accompanying drawings, a stapling machine 1 is illustrated which is in the form of a pliers-type stapling machine.

The stapling machine 1 incorporates a lower elongate component 2 carrying, at its forward end (i.e. to the left as shown in Figure 1) an anvil 3 adapted to clinch the lower end of staples ejected from an upper component 4 which is pivotally connected to the lower component about a pivot point 5.

The upper component 4 comprises a hollow housing which contains an elongate staple magazine 6 adapted to receive a "strip" of staples. A slidable pusher element 7 is associated with the magazine 6 and is associated with a spring element 8 which is adapted to bias the pusher element along the staple magazine 6 to bias staples therein towards an ejection slot 9 which is provided at the forward end of the component 4 substantially in alignment with the anvil 3.

A staple ejector blade 10 is provided which is movable through the ejection slot 9 to eject a staple, from the magazine, towards the anvil 3. The ejector blade 10 is movable within an appropriate guide slot provided within the housing, and the upper end of the ejector blade 10 is provided with an aperture 11 which receives the forward end of an ejector spring element 12.

The ejector spring element 12 is of "U" or "hair-pin" configuration and has a first substantially linear part 13, the end of which passes through the aperture 11, a curved portion 14 which extends around a locating pin 15, and a further linear portion 16 which extends parallel with the first linear part 13 but beneath that first part 13. An aperture 17 is formed in the first linear part, as can be seen in Figure 2. A toggle 18 is associated with the aperture.

The toggle 18 comprises an element which is mounted pivotally to pivot about a pivot axis 19 and is spring biased by means of a spring 20 to adopt a position in which the toggle is tilted to the left about the pivot axis 19 as shown in Figures 2 and 3. The toggle 18 has a projection 21 provided at its upper end adapted to pass through the aperture 17 and is also provided with a shoulder 22 adjacent the projection 21 which, in the initial condition of the toggle, is adapted to engage the under-surface of the linear portion 13 of the actuating spring 12 adjacent the aperture 17. It will be appreciated that with the toggle in the condition illustrated in Figure 1, a region of the actuating spring 12 adjacent the aperture 17 in the linear part 13 engages the shoulder 22, and thus that part of the spring cannot move downwardly. The upper part of the toggle 18 is, however, dimensioned to

pass through the aperture 17 when the toggle 18 is aligned with the aperture.

The toggle is provided with a projecting foot 23 which projects towards the right of the toggle adjacent the base of the toggle as shown in the accompanying drawings.

An actuating lever 24 is provided which is an elongate element having a first exposed actuating end portion 25 and a substantially centrally disposed pivot pin 26 which pivotally connects the actuating lever to the first component 2 which carries the anvil at a point substantially half-way between the pivot point 5 (between the first component 2 and the second component 4) and the anvil 3. The other end of the actuating lever 24 carries a roller 27 which engages the upper surface of the lower part 16 of the actuating spring 12.

It is to be observed that the length of the lower part 16 of the actuating spring 12 is such that if the lower part is moved downwardly the end of the lower part 16 of the actuating spring 12 will touch the foot 23 provided on the toggle 18.

A spring 18 is provided is provided engaging the actuating lever 24 and a stop 29 provided at the rear end of the second component 2 to bias the actuating lever downwardly. This has the effect of keeping the device in the condition shown in Figure 1 with the jaws open.

When the described device is to be utilised staples are located in the staple magazine and the staple pusher 7 will then, under the influence of the spring 8, bias the staples towards the ejection slot 9. A staple will therefore be present in the ejection slot 9 when the

stapling machine is in the condition illustrated in Figure 1 in which the staple ejector blade 10 is in an elevated condition.

The toggle 18 is tilted towards the left, as shown in the drawings, under the biasing effect of the spring 20, thus retaining the upper part of the actuating spring 12 in the upper position. A plurality of sheets of paper to be stapled together may be located between the component 2 carrying the anvil and the component 4, carrying the staple magazine and the staple ejector blade, and the rear part of the stapling machine (that is to say the part shown towards the right in Figure 1) is grasped with the upper rear part of the upper component 4 being received in the palm of the hand, and with the fingers engaging the operating part 25 of the actuating lever 24. As initial pressure is applied to the actuating lever 24, the lever pivots about the roller 27 against the bias of the spring 28. This serves to cause the lower component 2 to pivot about the pivot axis 5, moving the real location of the pivot axis 26. This movement of the lower component continues until the sheets of paper located between the upper component 4 and the lower component 2 have been gripped. A subsequent application of pressure to the actuating lever 24 causes the lever to pivot about the pivot axis 26. This causes the roller 27 to move towards the left (as shown in Figure 1) and downwardly. This causes the lower part 16 of the ejector spring 12 to move downwardly to the position shown in phantom in Figure 1. This downward movement of the lower portion of the spring 16 applies a significant force to the upper part of the spring tending to move the upper part of the spring downwardly. However, the upper part of the spring cannot move downwardly because of the action of the toggle 18.

When the lower part 16 of the spring 12 has moved downwardly by a certain extent, a significant force exists tending to bias the upper part 12 of the spring to move downwardly and then the end of the lower part of the spring engages the rearwardly extending foot 23 provided on the toggle 18. Further movement of the actuating lever 24 causes the toggle to pivot, in a clockwise sense, about the pivot axis 19, against the bias provided by the spring 20. When the toggle has pivotted, the shoulder 22 is aligned with the forward part of the aperture 17 and the upper part 13 of the actuator spring 12 can then move downwardly. The upper part of the toggle 18 thus passes through the aperture 17. The upper part of the actuator spring 12 is, of course, biased downwardly with a significant force because the lower part 16 of the spring has been moved downwardly by the roller 27.

Thus, the upper part 13 of the actuator spring 12 does move downwardly, forcing the staple ejector blade 10 downwardly through the ejection slot 9, causing a staple to be ejected through the slot 9. The ends of the arms of the staple are passed through the sheets of paper engaged between the upper component 4 and the lower component 2, and are clinched by the anvil 3.

The actuating lever is then released. The spring 28 which engages the interior of the actuating arm 24 and a stop 29 forces the actuating lever back to the initial condition. As the lever moves in a clockwise sense about the pivot point 26 as shown in Figure 1 the roller 27 engages the underside of the upper part 13 of the actuator spring 12. The entire spring thus rotates about the locating pin 15 until it returns to the initial position of Figure 1. The lower part of the spring thus also moves upwardly and under the influence of the biasing spring 20

the toggle returns to its initial condition. The described cycle of operation can then be repeated.

The prime advantage of a stapling machine as described above is that the staple is not ejected until the person actuating the machine has applied sufficient force to the actuating lever 24 to cause the above described chain of events to commence. Thus a predetermined amount of force has been stored in the stapling machine, because a predetermined deformation has been applied to the actuator spring 12. This force is selected to be sufficient to drive a staple through an appropriate number of sheets of paper. The device operates with an impulse or "click" so that the person operating the device is well aware of the fact that the device has operated to staple the sheets of paper together.

Referring to Figure 3 a modified embodiment of the invention comprises a stapling machine 31 which incorporates a lower elongate component 32 in the form of an anvil carrier which carries, at its forward end, an anvil 33 to clinch the lower ends of staples. The anvil 33 is retained in position by an anvil retaining spring 34, the spring defining an aperture 35 which engages a spigot 36 carried by the anvil carrier 32. One end of the spring 34 retains the anvil and the other end of the spring defines an upwardly extending arch 37 which engages the under-surface of a magazine carrier 38. The magazine carrier is of channel-form. The side walls 39 of the magazine carrier terminate, at the forward end, with inwardly directed flanges 40 and the side walls of the magazine carrier define arcuate apertures 41. One side wall of the magazine carrier, as visible in Figure 3 defines an aperture 42 which forms a "window". Contained within the magazine carrier 38 is a magazine 43 having side walls 44, the side

walls terminating at the forward end with inwardly directed flanges 45. The magazine is adapted to receive a strip of staples. Slidably mounted within the magazine is a staple pusher 46 which is moulded integrally of plastic and which has an upstanding projection 47 adapted to engage a constant tension spring 48. The constant tension spring comprises two end portions 49 which each terminate with a spiral portion 50, these portions 49 being inter-connected by an intermediate piece 51. The intermediate piece 51 is adapted to engage the abutment 47 provided on the staple pusher 46. The spiral portions are adapted to engage a spring guide 52 which in turn is adapted to be received within an appropriate cavity formed in the under-surface of a staple steady 53. The staple steady is adapted to lie over staples present in the magazine. The staple steady 53 is provided with a lug 54 and the side walls of the magazine holder 38 are provided with lugs 55, the lugs 54 and 55 being adapted to engage trunions 56 provided for that purpose on the anvil holder 32.

The staple steady 53 defines an aperture 57 in its side wall adapted to be co-aligned with the aperture 42 in the side wall of a magazine holder 38.

A toggle 58 is provided having a bore 59 therethrough adapted to receive a pin which also passes through apertures 60 formed in upstanding wall portions provided on the top of the staple steady 53. The toggle is thus pivotally mounted in position. The toggle may be spring biased by means of an appropriate spring as in the manner of the toggle 18 described with reference to Figure 1. The upper part of the toggle is provided with a projection 61 adapted to pass through an aperture 62 formed in the upper part 63 of a spring 64 of "U" or "hair-pin" configuration, the lower arms 65 of the spring being of

lesser extent than the upper arm 63. The spring is adapted to be received on top of the staple steady 53.

A cover 66 is provided adapted to be mounted over the components described above, the cover 66 presenting a window or aperture 67 in the side thereof adapted to be co-aligned with the apertures 42 and 57 described below. A release catch 68 is provided which is associated with a release catch clip 69 so that the release catch clip can be mounted on the front of the cover.

A staple ejector blade 70 is provided defining an aperture therein 71 which engages a projection 72 provided at the forward end of the upper arm 63 of the spring 64.

A carrier front plate 73 is provided adapted to be mounted on the carrier.

A lower actuating lever 74 is provided which has, substantially at its mid-point, a bearing 75 which is adapted to be received within a recess 76 provided at the mid-point of the anvil carrier 32. A roller 76 is provided at the forward end of the actuating lever 74, the roller passing through the arcuate slots 41 and engaging the upper surface and the lower part 65 of the spring 64.

It is to be appreciated that by actuating the catch 68 the magazine may be moved forwardly so it projects from the housing 66, enabling the supply of staples within the magazine to be replenished.

When the magazine is pushed back into the housing the staple ejector 47 will engage the portion 51 of the spring 48, and as the staple ejector is moved further towards the right as shown in Figure 1 the spiral

portions 51 of the spring will tend to unwind, thus placing the spring under tension and applying a bias to the staple ejector 46 tending to move the staple ejector towards the left, thus biasing staples towards the ejection slot.

In an initial condition the toggle 58 is in a forward position, with the projection 61 passing through the aperture 62 and the shoulder, adjacent the projection, engaging the upper arm 63 of the spring. When pressure is applied to the actuating lever 74 the anvil carrier will tend to move pivotally upwardly thus gripping any paper located between the anvil and the magazine holder, and also the lower part 65 of the spring will tend to move downwardly, due to the force applied thereto by the roller 76. When the lower end of the spring engages the projecting foot provided on the toggle, the toggle will be pivotted, enabling the upper part 63 of the spring to move downwardly under the bias applied thereto due to the tension present in the spring 64. The staple ejector blade will thus move downwardly swiftly, causing a staple to be ejected.

The spring 48 may have markings present on the part thereof that forms the coil 50 adjacent the apertures 42 and 57 when the supply of staples is about to be exhausted. This marking will then be visible through a slit 52' provided for that purpose in spring guide 52, the aperture or window 67 formed in the housing 66 to provide an indication that the supply of staples is about to be exhausted.

Whilst the invention has been described by way of example with reference to one embodiment it is to be appreciated that many modifications may be effected without departing from the scope of the invention as defined by the

following Claims. For example, whilst the invention has been described with reference to an embodiment in which there is a single window provided on one side of the main housing 31 to enable the stages of the supply of staples to be observed, in a modified embodiment two windows may be provided, one on each side of the housing. Thus the status of the supply of staples may be observed from either side of the housing.

CLAIMS:

1. A stapling machine for stapling together sheets of paper or the like, the stapling machine comprising a first component carrying an anvil adapted to clinch the ends of the arms of the staple, which is pivotally connected to a second component containing a magazine for staples, means defining a staple ejection slot, means for biasing staples within the magazine towards the staple ejection slot, and a staple ejector blade adapted to move through the staple ejection slot to eject a staple towards the anvil, the staple ejector blade being associated with an actuator element adapted to move the ejector blade, the actuator element being provided with means to retain the actuator spring in a first predetermined position until a predetermined force has been applied to the actuator element tending to bias the ejector blade downwardly, means being provided then to release the actuator element to permit the actuator element to move, driving the staple ejector blade.
2. A stapling machine according to Claim 1 wherein the means adapted to retain the actuator element in position comprise a toggle having part adapted to engage part of the actuator element, the toggle being adapted to be moved to a position in which the toggle does not engage the spring when said predetermined force has been applied to the actuator element.
3. A stapling machine according to Claim 2 wherein the toggle is resiliently biased towards a position in which it engages the actuator element.

4. A stapling machine according to Claim 2 or Claim 3 wherein the actuating element is a spring of substantially "U" shape, presenting two substantially parallel arms, one arm being connected to the staple ejection blade and being associated with the said toggle, the other arm being movable, away from the first arm actuating element, to apply said predetermined force to the first element, means being provided to operate the toggle when the said other arm has been moved to apply said predetermined force.
5. A stapling machine according to Claim 4 wherein the toggle is provided with means adapted to engage the free end of the said other arm of the actuator spring when the actuator spring has been moved to apply said predetermined extent.
6. A stapling machine according to Claim 4 or 5 in the form of a pliers stapling machine, the stapling machine incorporating a manually operable actuating lever which is pivotally connected to the first component and which engages said actuator spring to effect operation of the stapling machine.
7. A stapling machine according to Claim 6 wherein the actuating lever has roller means engaging the said other arm of said actuator spring.
8. A stapling machine according to Claim 7 wherein said roller means also engage the first arm of said actuator spring, and the actuating handle is provided with resilient means adapted to bias the actuating handle to an initial position, so that as the handle is biased towards the initial position the roller engages the actuating spring and moves the actuating spring to an initial position.

9. A stapling machine substantially as herein described with reference to and as shown in Figures 1 and 2 of the accompanying drawings.

10. A stapling machine substantially as herein described with reference to and as shown in Figure 3 of the accompanying drawings.

11. Any novel feature or combination of features disclosed herein.

Carbide and steel




FIG. 1




Fig 2




FIG-3

EXPLODED VIEW